YSHIELD GmbH & Co. KG, Rotthofer Straße 1, 94099 Ruhstorf, Germany Phone:0049-8531-31713-0, Email:info@yshield.com, Web:www.yshield.com

HSF64 - Shielding paint (HF+LF)

DISPERSION SILICATE WITHOUT PRESERVATION



YSHIELD® HSF64

40 GHz 20 d 30 dE 40 dB 50 dE 70 d 30 di

Abschirmung Okologie Attenuation -cology Härte Hardness

90 dE

As shielding paint for rooms and buildings

Shielding paint for shielding high-frequency radiation (HF) and low-frequency electric fields (LF).

Dispersion silicate paint without preservation agent. **Minimalistic formulation with** small limitations at hardness, adhesion and shielding. Improved again 2019.

Breathable, solvent-free, plasticizer-free, low-emission and without preservation agent.

<u>Underground</u>

Adhesion on almost all absorbent substrates interior.

Top coating

Preferably covered with plastic bonded water-based emulsion **paints**, dispersion silicate paints or silicon resin paints.

Grounding

Must be grounded! We recommend interior the **grounding** strap EB2 plus grounding plate GW.

Screening attenuation

Single layer 32 dB Double layer 40 dB Three layer 48 dB

Frost resistance

This product is frost resistant (proved for 5 frost-/thaw cycles) and can be shipped throughout the year by air cargo or ship.

Ingredients

Water, potassium silicate, natural graphite, carbon black, pure acrylics dispersion, additives, NO preservation agent.

Technical data

Please find detailled data in the table overview and the technical data sheet.

Ready for 5G

Our shielding paints have an almost linear screening attenuation for a very large frequency range including both 5G frequency spectrums FR1 (600 MHz - 6 GHz) and FR2 (24 GHz - 40 GHz).

Safety up to 40 GHz

We have a professional EMC-laboratory according to various standards up to 40 GHz on site. You'll find the measuring curves and reports from 40/600 MHz - 40 GHz in the internet on the corresponding product pages.

No nanotechnology

Our shielding paints are developed in accordance with strict ecological criteria. We use the carbon black with the lowest emission possible on the market and untreated natural graphite. We consciously do not use graphene, a nanomaterial where the hazard potential is still completely unknown.

YSHIELD®

TÜV-SÜD certification

We have our shielding paints monitored by TÜV-Süd. The whole production process including quality control, emission behaviour and economical use of preserving agents is subject to monitoring.

